



PART NUMBER: 0009A3000-30-270

V/UHF LOS, UHF SATCOM & GPS Multi-Purpose Vented Hatch System (MPVHS)

- ► BILLET ALUMINUM CONSTRUCTION
- ► NO MODIFICATION TO AIRCRAFT
- ► FIELD REPLACEABLE SEALS AND HARDWARE
- ► FAA/DOD CERTIFIED
- ► HI ANGLE UHF SATCOM
 CONTINUOUS LO ANGLE FREQUENCY
 COVERAGE, 30-2000 MHZ
- ▶ L1 AND L2 GPS



R4 provides a complete "Turn Key" solution to include a Portable Airborne Communication Terminal (PACT) that provides full 30—2000 MHz LOS, BLOS, Voice/Data capability with an integrated Intercommunication System for multiple operators, aircraft interface/control, and ground station capability.



SPECIFICATIONS		
ELECTRICAL		
Frequency	UHF Hi Angle : 240 - 385 MHz V/UHF/L-Band Lo Angle : 30 - 2000 MHz GPS: 1564 - 1587 / 1216 - 1239 MHz	
Gain (typical)		+6.5 dBiC @ Zenith -18.5 dBi @ 30 MHz
		-8.0 dBi @ 88 MHz -1.0 dBi average 118-174 MHz +1.0 dBi average 225 - 2000 MHz
	GPS:	+4.0 dBiC @ Zenith
RF Power	W. 10	200 Watts CW 50 Watts VHF 200 Watts (225-2000 MHz) 1 Watt
MECHANICAL		19
Height Above Aircraft	12.6 Inches	
Weight	52 LBS	

www.r4-integration.com

Email: info@r4-integration.com